

# Sandwich Hydraulic Diaphragm

# SR series SD type

## Spring Return Sandwich Hydraulic Diaphragm Dosing Pump

SD Sandwich Hydraulic diaphragm metering pumps are normally used when:

- The dosed liquid contains small amounts of suspended solids
- No leakage are accepted
- The dosed liquid is a toxic solution
- High pressure is required

Each pump is fitted with a standard gearbox reduction system with a vertical mounted motor.

The reduction gearbox is of a standard endless screw plus worm-wheel type, supported by bearing, fully lubricated in oil bath.

Stroke adjustment can be carried with the pump at rest or in operation and it can be manual or automatic through automatic actuator driven by 4-20 mA; different BUS; pneumatic.


A built-in safety valve is installed in the hydraulic circuit, in order to protect the diaphragm against over pressure. The peculiarity of this pump is the special sandwich diaphragm and the reliability of the diaphragm rupture detection system.

Furthermore they comply with ATEX standard, therefore they can be installed in Hazardous area.

Wide choice of wetted materials: S.S.316L; PVC; PP; PVDF; PTFE other materials available upon request.

## Fittings

- Polyethylene tanks
- Relief valves and back pressure valves
- Safety relief valve
- Injection valve
- Foot valve
- Pulsation dampeners
- Calibration pot



Model	Max Capacity in Lt/h	Max pressure in Barg
SD 125N	108	13.5
SD 175N	418	14
SD 250N	1068	7.2
AP SD 125N	60	40
AP SD 175N	247	40
AP SD 250N	556	20.7